

# REPORT DOCUMENTATION PAGE

Form Approved  
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.

1. REPORT DATE (DD-MM-YYYY) 26-11-2002		2. REPORT TYPE Technical Paper		3. DATES COVERED (From - To) 20-23 July 2003	
4. TITLE AND SUBTITLE Development of GOX/Hydrocarbon Multi-element Swirl Coaxial Injector Technology				5a. CONTRACT NUMBER F04611-01-C-0010	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S) Johnson, C.W.; Muss, J.; Cheng, G.C.; Davis, R.; Cohn, R.K.				5d. PROJECT NUMBER BMDO	
				5e. TASK NUMBER SBRU	
				5f. WORK UNIT NUMBER 549926	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Sierra Engineering, Inc. 603 East Robinson Street, Suite 7 Carson City, NV 89701-4046				8. PERFORMING ORGANIZATION REPORT	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) Air Force Research Laboratory (AFMC) AFRL/PRSA 5 Pollux Drive Edwards AFB CA 93524-7048				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S NUMBER(S) AFRL-PR-ED-AB-2002-289	
12. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.					
13. SUPPLEMENTARY NOTES					
14. ABSTRACT  (See attached)					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT  A	18. NUMBER OF PAGES  1	19a. NAME OF RESPONSIBLE PERSON Leilani Richardson
a. REPORT Unclassified	b. ABSTRACT Unclassified	c. THIS PAGE Unclassified			19b. TELEPHONE NUMBER (include area code) (661) 275-5015

20030116 086

MEMORANDUM FOR PRS (Contractor Publication)

FROM: PROI (STINFO)

26 Nov 2002

SUBJECT: Authorization for Release of Technical Information, Control Number: **AFRL-PR-ED-AB-2002-289**  
C.W. Johnson (Sierra) et al., "Development of GOX/Hydrocarbon Multi-element Swirl Coaxial Injector  
Technology" (abstract only)

**AIAA Joint Propulsion Meeting**  
**(Huntsville, AL, 20-23 July 2003)**

**(Statement A)**

## Development of GOX/Hydrocarbon Multi-element Swirl Coaxial Injector Technology

C.W. Johnson and Jeff Muss, Sierra Engineering, Inc.

G.C. Cheng, ME Dept., UAB

Rory Davis, Convergence Engineering

R.K. Cohn, AFRL, Edwards AFB, CA

### ABSTRACT

In developing the advanced liquid rocket engine, injector design is critical to obtaining the dual goals of long engine life as well as providing high-energy release efficiency in the main combustion chamber. Introducing a swirl component in the injector flow can enhance the propellant mixing and thus improve engine performance. Therefore, swirl coaxial injectors, which swirl liquid fuel around a gaseous oxygen core, show promise for the next generation of high performance staged combustion rocket engines utilizing hydrocarbon fuels. Understanding the mixing and combustion characteristics of the swirl coaxial flow provides the insight of optimizing the injector design. A joint effort of Sierra Engineering (Sierra) and the Propulsion Directorate of the Air Force Research Lab (AFRL) was conducted to develop a design methodology, utilizing both high-pressure cold-flow testing and uni-element hot-fire testing, to create a high performing, long life swirl coaxial injector for multi-element combustor use. Several swirl coax injector configurations designed and fabricated by Sierra have been tested at AFRL. The cold-flow tests and numerical simulations have been conducted. The cold flow result provided valuable information of flow characteristics of swirl coaxial injectors. However, there are two important flow features of liquid rocket engines missed from the cold flow test: 1) the effect of combustion on the propellant mixing, and 2) the interaction of multiple injectors. The present work studies the hot flow environment specifically the multiple element swirl coaxial injector. Numerical simulations were performed with a pressure-based computational fluid dynamics (CFD) code, FDNS. CFD results produced loading environments for an ANSYS finite element thermal/structural model. Since the fuels are injected at temperature below its critical temperature, the effect of phase change and chemical reactions needs to be accounted for in the CFD model. A homogeneous spray approach with a real-fluid property model was employed in the FDNS code to simulate the spray combustion phenomena over a wide range of operating conditions. Numerical results will be reported in the full-length paper. Future work, which will not be presented in this paper, will compare these numerical results to planned hot fire test results.

**DISTRIBUTION STATEMENT A**  
Approved for Public Release  
Distribution Unlimited